

Stormwater Management Plan Instructions: To Accompany All Grading Permit Applications

In order to comply with the federal Clean Water Act, the state Water Code and County Ordinances, the County of San Diego requires that property owners complete a Stormwater Management Plan prior to issuance of any Grading Permit. The purpose of a Stormwater Management Plan is to document Best Management Practices (BMPs) that will be implemented to prevent pollutants (including sediment) from entering stormwater conveyances and receiving waters. The Stormwater Management Plan becomes a part of the Grading Permit and is subject to enforcement by County inspectors and others.

Stormwater Management Plans include the elements described in the following sections:

Section 1: Required Information - This section is used to provide the County with basic information necessary to evaluate and prioritize project activities. Each of the items in this section must be completed, except projects with less than 5 acres of disturbed area are not required to have a Waste Discharge Identification Number (WDID). Grading projects with a disturbed area of greater than 5 acres must also meet additional requirements from the State Water Resources Control Board (SWRCB). Those additional requirements include filing a Notice of Intent (NOI) and preparation of a Stormwater Pollution Prevention Plan (SWPPP).

Please note that watercourses and waterbodies include ephemeral drainages (i.e., those that are dry during part of the year).

<u>Section 2: Best Management Practices</u> - Best Management Practices (BMPs) must be selected and implemented to prevent erosion and construction-related materials, sediment, wastes and spills from entering stormwater conveyances and receiving waters.

Note: It is the responsibility of the property owner and the contractor to determine the types of BMPs that will be used, as well as the levels of application necessary to comply with the County's Stormwater and Grading Ordinances. Failure to prevent soil erosion and discharges of sediment and other pollutants from construction sites is subject to enforcement by the County or others. At a minimum, the County requires that the BMPs listed in Table A (attached) be installed and maintained for all grading projects. Additional BMPs listed in Table B (attached) may also be required in correlation to a project's scope, potential for discharges and proximity to a watercourse or other receiving waters.

Section 3: Certification – The property owner must sign this section certifying that they understand the County's minimum requirements for stormwater management of construction activities and will implement, monitor and maintain the selected BMPs to ensure their effectiveness.

A County BMP manual can be found at the DPW and DPLU Permit Counters. The Manual includes all of the referenced BMPs listed in Tables A and B and from the *Caltrans Storm Water Quality Handbooks* and *California Stormwater BMP Handbook for Construction*. The entire manuals may also be ordered directly from the following sources:

Caltrans Manuals Caltrans Publications unit (916)445-3520 (916)324-8997 Fax CA Stormwater BMP handbook BPS Reprographic Services 1700 Jefferson St Oakland, CA, 94612 (510)287-5485 (510)444-1262 Fax



County of San Diego STORMWATER MANAGEMENT PLAN

This form must be submitted with all Grading Permit Applications.

SECTION 1. Required Information Project Name: Project Name: Project Name: Project Contact Person: Project Contact Person: Project Contact Person: Project Contact Person: Project diddress or location: Project finish date: Project start date: Project finish date: Project finish date: Project start date: Project finish date: Project start date: Project finish date: Project finish date: Project finish date: Project finish date: Project start date: Project finish d	This form must be submitte	u with an Grauing I trimit Application	13.						
Project Address or location: Title: Phone #: APN #: Grading start date: Grading fimish date: Project start date: Project fimish date: Estimated amount of disturbed acreage: acres (If equal to or greater than 5 acres, you must also provide a WDID number from the SWRCB.) WDID Are there any watercourses or waterbodies within 50 feet of the limits of soil disturbance? YES NO Does the woil type have high crossion potential (fine grain soil like sand, slit, fine distintegrated grantite)? YES NO Does the project site have or propose slopes higher than 25 feet or steeper than 1:1? YES NO SECTION 2. Best Management Practices Best Management Practices Best Management Practices Rest Management planning is to reduce pollution to the maximum extent practicable by implementing. Best Management Practices of MBPs. The resion control practices, and; 2) Velocity reduction, and; 3) Sediment control practices, and; 4) Offsite sediment tracking control, and; 5) General site and materials management. BMPs from each of the five categories must be used together as a system in order to prevent resion, sediment, wastes, spills, and residues from leaving the site. Meeting the strength of the property owner and the contractor to determine the types of BMPs that will be used, as well as the levels of application necessary to comply with the County's Stormwater and Grading Ordinances. Best Management Practice Tables Tables A and B (attached) must be used to indicate those BMPs that will be used to prevent stormwater pollution. At a minimum, the County equires that the BMPs listed in Table A be installed on all grading projects. However, some BMPs may not be applicable to every project. For example, if storm drain inlets are not present, then Storm Drain Inlet Protection (BMP SCI0) would not be applicable. Grading Plan Best Management Practice Checklist The following information shall be shown on the grading plans: The following information shall be shown on the grading plans: The follo	SECTION 1. Required Inf	ormation							
Title: Phone #: APN #: Grading start date: Project Contact Person: Grading finish date: Project start date: Project start date: Project finish date: Estimated amount of disturbed acreage: acres (If equal to or greater than 5 acres, you must also provide a WDID number from the SWRCB, WDID Are there any watercourses or waterbodies within 50 feet of the limits of sold disturbance? YES	Grading Permit Application Numbe	r:	Project Name:						
Estimated amount of disturbed acreage: acres (If equal to or greater than 5 acres, you must also provide a WDID number from the SWRCB.) WDID	Name of Project Contact Person:		Project address or location:						
Estimated amount of disturbed acreage: acres (If equal to or greater than 5 acres, you must also provide a WDID number from the SWRCB.) WDID	Title:	Phone #:		APN #:					
Are there any watercourses or waterbodies within 50 feet of the limits of soil disturbance? YES NO Does the soil type have high erosion potential (fine grain soil like sand, slif, fine disintegrated grantle)? YES NO Does the project site have or propose slopes higher than 25 feet or steeper than 1:1? YES NO SECTION 2. Best Management Practices Best Management Practices Best Management Practices The goal of stormwater management planning is to reduce pollution to the maximum extent practicable by implementing Best Management Practices (BMPs). There are five categories make the sediment tracking control, and; 5) General site and materials management. BMPs from each of the five categories must be used together as a system in order to prevent pollutants (including sediment) from leaving the site. When properly implemented, monitored and maintained, BMPs will function to prevent pollutants (including sediment) from leaving the site. It is the responsibility of the property owner and the contractor to determine the types of BMPs that will be used, as well as the levels of application necessary to comply with the County's Stormwater and Grading Ordinances. Best Management Practice Tables Tables A and B (attached) must be used to indicate those BMPs that will be used to prevent stormwater pollution. At a minimum, the County requires that the BMPs listed in Table A be installed on all grading projects. However, some BMPs may not be applicable to every project. For example, if storm drain inlets are not present, then Storm Drain Inlet Protection (BMP SC10) would not be applicable. Grading Plan Best Management Practice Checklist The fooltprint of any existing structures and facilities. The footprint of any existing structures and facilities to be constructed. The finity of project boundaries. The footprint of any existing structures and facilities to be constructed. The footprint of any existing structures and facilities to be constructed. The footprint of any existing struc	Grading start date:	Grading finish date:	Project start date:	Project finish date:					
Does the soil type have high erosion potential (fine grain soil like sand, silt, fine disintegrated granite)? YESNO Does the project site have or propose slopes higher than 25 feet or steeper than 1:1? YESNO SECTION 2. Best Management Practices Best Management Practices Best Management Practices The goal of stormwater management planning is to reduce pollution to the maximum extent practicable by implementing Best Management Practices (BMPs). There are five categories of BMPs: 1) Erosion control practices, and; 2) Velocity reduction, and; 3) Sediment control practices, and; 4) Offsite sediment tracking control, and; 5) General site and materials management. BMPs from each of the five categories must be used together as a system in order to prevent erosion, sediment, wastes, spills, and residues from leaving the site. When properly implemented, monitored and maintained, BMPs will function to prevent pollutants (including sediment) from leaving the site. It is the responsibility of the property owner and the contractor to determine the types of BMPs that will be used, as well as the levels of application necessary to comply with the County's Stormwater and Grading Ordinances. Best Management Practice Tables Tables A and B (attached) must be used to indicate those BMPs that will be used to prevent stormwater pollution. At a minimum, the County requires that the BMPs listed in Table A be installed on all grading projects. However, some BMPs may not be applicable to every project. For example, if storm drain inlets are not present, then Storm Drain Inlet Protection (BMP SC10) would not be applicable. Grading Plan Best Management Practice Checklist The following information shall be shown on the grading plans: G The footprint of any existing structures and facilities. G The footprint of any existing structures and facilities. G The footprint of any existing structures and facilities. G The location(s) where runoff from the site may enter storm drain(s), channel(s), and/or receiving water	Estimated amount of disturbed acrea								
Does the soil type have high erosion potential (fine grain soil like sand, silt, fine disintegrated granite)? YESNO Does the project site have or propose slopes higher than 25 feet or steeper than 1:1? YESNO SECTION 2. Best Management Practices Best Management Practices Best Management Practices The goal of stormwater management planning is to reduce pollution to the maximum extent practicable by implementing Best Management Practices (BMPs). There are five categories of BMPs: 1) Erosion control practices, and; 2) Velocity reduction, and; 3) Sediment control practices, and; 4) Offsite sediment tracking control, and; 5) General site and materials management. BMPs from each of the five categories must be used together as a system in order to prevent erosion, sediment, wastes, spills, and residues from leaving the site. When properly implemented, monitored and maintained, BMPs will function to prevent pollutants (including sediment) from leaving the site. It is the responsibility of the property owner and the contractor to determine the types of BMPs that will be used, as well as the levels of application necessary to comply with the County's Stormwater and Grading Ordinances. Best Management Practice Tables Tables A and B (attached) must be used to indicate those BMPs that will be used to prevent stormwater pollution. At a minimum, the County requires that the BMPs listed in Table A be installed on all grading projects. However, some BMPs may not be applicable to every project. For example, if storm drain inlets are not present, then Storm Drain Inlet Protection (BMP SC10) would not be applicable. Grading Plan Best Management Practice Checklist The following information shall be shown on the grading plans: G The footprint of any existing structures and facilities. G The footprint of any existing structures and facilities. G The footprint of any existing structures and facilities. G The location(s) where runoff from the site may enter storm drain(s), channel(s), and/or receiving water	Are there any watercourses or water	hodies within 50 feet of the limits of soil disturba	nce? VES NO						
Best Management Practices Best Management Practices The goal of stormwater management planning is to reduce pollution to the maximum extent practicable by implementing Best Management Practices (BMPs). There are five categories of BMPs: 1) Erosion control practices, and; 2) Velocity reduction, and; 3) Sediment control practices, and; 4) Offsite sediment tracking control, and; 5) General site and materials management. BMPs from each of the five categories must be used together as a system in order to prevent erosion, sediment, wastes, spills, and residues from leaving the site. When properly implemented, monitored and maintained, BMPs will function to prevent pollutants (including sediment) from leaving the site. It is the responsibility of the property owner and the contractor to determine the types of BMPs that will be used, as well as the levels of application necessary to comply with the County's Stormwater and Grading Ordinances. Best Management Practice Tables Tables A and B (attached) must be used to indicate those BMPs that will be used to prevent stormwater pollution. At a minimum, the County requires that the BMPs listed in Table A be installed on all grading projects. However, some BMPs may not be applicable to every project. For example, if storm drain intels are not present, then Storm Drain Inlet Protection (BMP SC10) would not be applicable to every project. For example, if storm drain inlets are not present, then Storm Drain Inlet Protection (BMP SC10) would not be applicable. Grading Plan Best Management Practice Checklist The following information shall be shown on the grading plans: The footprint of all structures and facilities to be constructed. The finite of grading. The footprint of all structures and facilities to be constructed. The footprint of any existing structures and facilities to be constructed. The limits of grading. The location(s) where runoff from the site may enter storm drain(s), channel(s), and/or receiving waters. Please note that each of the items identified									
Best Management Practices The goal of stormwater management planning is to reduce pollution to the maximum extent practicable by implementing Best Management Practices (BMPs). There are five categories of BMPs: 1) Erosion control practices, and: 2) Velocity reduction, and: 3) Sediment control practices, and: 4) Offsite sediment tracking control, and; 5) General site and materials management. BMPs from each of the five actegories must be used together as a system in order to prevent erosion, sediment, wastes, spills, and residues from leaving the site. When properly implemented, monitored and maintained, BMPs will function to prevent pollutants (including sediment) from leaving the site. It is the responsibility of the property owner and the contractor to determine the types of BMPs that will be used, as well as the levels of application necessary to comply with the County's Stormwater and Grading Ordinances. Best Management Practice Tables Tables A and B (attached) must be used to indicate those BMPs that will be used to prevent stormwater pollution. At a minimum, the County requires that the BMPs listed in Table A be installed on all grading projects. However, some BMPs may not be applicable to every project. For example, if storm drain inlets are not present, then Storm Drain Inlet Protection (BMP SC10) would not be applicable. Grading Plan Best Management Practice Checklist The following information shall be shown on the grading plans: Q The project boundaries. Q The from the site may enter storm drain(s), channel(s), and/or receiving waters. Q The location(s) where runoff from the site may enter storm drain(s), channel(s), and/or receiving waters. Please note that each of the items identified by a star («) in Tables A and B must be included on the grading plans, and labeled with the designation found in the tables (for example, SS-7). SECTION 3. Certification The following certification must be signed before a Grading Permit will be issued. I have read and understand that the County of San Diego		-)					
Best Management Practices The goal of stormwater management planning is to reduce pollution to the maximum extent practicable by implementing Best Management Practices (BMPs). There are five categories of BMPs: 1) Erosion control practices, and; 2) Velocity reduction, and; 3) Sediment control practices, and; 4) Offsite sediment tracking control, and; 5) General site and materials management. BMPs from each of the five actegories must be used together as a system in order to prevent erosion, sediment, wastes, spills, and residues from leaving the site. When properly implemented, monitored and maintained, BMPs will function to prevent pollutants (including sediment) from leaving the site. It is the responsibility of the property owner and the contractor to determine the types of BMPs that will be used, as well as the levels of application necessary to comply with the County's Stormwater and Grading Ordinances. Best Management Practice Tables Tables A and B (attached) must be used to indicate those BMPs that will be used to prevent stormwater pollution. At a minimum, the County requires that the BMPs listed in Table A be installed on all grading projects. However, some BMPs may not be applicable to every project. For example, if storm drain inlets are not present, then Storm Drain Inlet Protection (BMP SC10) would not be applicable. Grading Plan Best Management Practice Checklist The following information shall be shown on the grading plans: Q The project boundaries. Q The from the site may enter storm drain(s), channel(s), and/or receiving waters. Q The location(s) where runoff from the site may enter storm drain(s), channel(s), and/or receiving waters. Please note that each of the items identified by a star («) in Tables A and B must be included on the grading plans, and labeled with the designation found in the tables (for example, SS-7). SECTION 3. Certification The following certification must be signed before a Grading Permit will be issued. I have read and understand that the County of San Diego	Does the project site have or propos	e slopes higher than 25 feet or steeper than 1:1?	YES NO						
The goal of stormwater management planning is to reduce pollution to the maximum extent practicable by implementing Best Management Practices (BMPs). There are five categories of BMPs: 1) Erosion control practices, and; 2) Velocity reduction, and; 3) Sediment control practices, and; 4) Offsite sediment tracking control, and; 5) General site and materials management. BMPs from each of the categories must be used together as a system in order to prevent erosion, sediment, wastes, spills, and residues from leaving the site. When properly implemented, monitored and maintained, BMPs will function to prevent pollutants (including sediment) from leaving the site. It is the responsibility of the property owner and the contractor to determine the types of BMPs that will be used, as well as the levels of application necessary to comply with the County's Stormwater and Grading Ordinances. **Best Management Practice Tables** Tables A and B (attached) must be used to indicate those BMPs that will be used to prevent stormwater pollution. At a minimum, the County requires that the BMPs listed in Table A be installed on all grading projects. However, some BMPs may not be applicable to every project. For example, if storm drain inlets are not present, then Storm Drain Inlet Protection (BMP SC10) would not be applicable. **Grading Plan Best Management Practice Checklist** The following information shall be shown on the grading plans: **Q** The footprint of any existing structures and facilities.** Q** The footprint of any existing structures and facilities to be constructed.** Q** The limits of grading.** Q** The limits of grading.** Q** The location(s) where runoff from the site may enter storm drain(s), channel(s), and/or receiving waters.** Please note that each of the items identified by a star (**) in Tables A and B must be included on the grading plans, and labeled with the designation found in the tables (for example, SS-7). **SECTION 3.** Certification must be signed before a Grading Permit will be issued.**	SECTION 2. Best Managen	nent Practices							
The following certification must be signed before a Grading Permit will be issued. I have read and understand that the County of San Diego has adopted minimum requirements for stormwater management of construction activities. I certify that the BMPs I have selected in Tables A and B will be implemented to effectively minimize the potentially negative impacts of this project's construction activities on stormwater quality. I further agree to install, monitor, maintain or revise the selected BMPs to ensure their effectiveness. I also understand that non-compliance with the County's Stormwater and Grading Ordinances may result in enforcement by the County, including fines,	The goal of stormwater manageme (BMPs). There are five categories sediment tracking control, and; 5) Corder to prevent erosion, sediment, function to prevent pollutants (inclutypes of BMPs that will be used, as Best Management Practice Tables Tables A and B (attached) must be requires that the BMPs liste every project. For example, if storm Grading Plan Best Management For The following information shall be seed The project boundaries. Chapter The footprint of any existing storm The footprint of all structures and The limits of grading. Chapter The limits of grading. Chapter The location(s) where runoff for Please note that each of the items identification.	of BMPs: 1) Erosion control practices, and; 2) Volumeral site and materials management. BMPs from the site and materials management. BMPs from the site and residues from leaving the site. It is the research was the levels of application necessary to compare the site at the levels of application necessary to compare the site and indicate those BMPs that will be used at drain inlets are not present, then Storm Drain Interactice Checklist shown on the grading plans: Tructures and facilities. The site along with any intermediate grades from the site may enter storm drain(s), channel(s), and the site may enter storm drain(s).	elocity reduction, and; 3) Sedimentom each of the five categories must When properly implemented, mon ponsibility of the property owner apply with the County's Stormwater at to prevent stormwater pollution. In projects. However, somet Protection (BMP SC10) would not that will significantly affect site drand/or receiving waters.	t control practices, and; 4) Offsite st be used together as a system in itored and maintained, BMPs will and the contractor to determine the and Grading Ordinances. At a minimum, the County are BMPs may not be applicable to not be applicable.					
I have read and understand that the County of San Diego has adopted minimum requirements for stormwater management of construction activities. I certify that the BMPs I have selected in Tables A and B will be implemented to effectively minimize the potentially negative impacts of this project's construction activities on stormwater quality. I further agree to install, monitor, maintain or revise the selected BMPs to ensure their effectiveness. I also understand that non-compliance with the County's Stormwater and Grading Ordinances may result in enforcement by the County, including fines,	SECTION 3. Certification								
	ative impacts of this project's ensure their effectiveness.								

−Date −

Property owner_

TABLE A: MINIMUM REQUIRED CONSTRUCTION BMPs

IADLE A: MINIMU) 1 VI 1 N.	EQUIN	ED CO.	11511	1001	TON DIVITS
Minimum Required Best		NS eer ks (Nov '01)	a Storm- IP k for tion	Will BMP Be Used?		If No, State
Management Practices	(«) If used, these BMPs must be shown on the grading plan.	CALTRANS Stormwater Quality Handbooks (Nov '01)	California Stor water BMP Handbook for Construction	Yes	No	Reason
1. A. Erosion Control - Slopes	Must	select on	e (more if	fneede	ed)	
Vegetation Stabilization Planting (see note 1)	«	SS-2 SS-4	ESC10			
Hydraulic Stabilization Hydroseeding (see note 1)	«	SS-3 SS-4	ESC10			
Bonded Fiber Matrix (see note 2)	«	SS-4	ESC11			
Physical Stabilization Erosion Control Blanket(see note 2)	«	SS-7	ESC20			
1. B. Erosion Control - Flat Areas(< 5%)	Must	select one	e (more if	f neede	ed)	
Will use above Slope Control measures on flat areas also	«	SS- 2,3,4,7	ESC10, 11,20			
Mulch, straw, wood chips, soil application	«	SS-6 SS-8	-			
2. Velocity Reduction	Must	select on	e			
Energy Dissipater Outlet Protection (see note 3)	«	SS-10	ESC40			
3. Sediment Control	Must	select one	e (more if	f neede	ed)	
Silt Fence	«	SC-1	ESC50			
Straw Wattles	«	SC-5	-			
Gravel Bags	«	SC-6 SC-8	ESC52			
Storm Drain Inlet Protection	«	SC-10	ESC54			
Desilting Basin (not used on DPLU permits)	«	SC-2	-			
4. Offsite Sediment Tracking Control	Must	select on	e (more if	f neede	d)	
Stabilized Construction Entrance	«	TC-1	ESC24			
Construction Road Stabilization	«	TC-2	ESC23			
Entrance / Exit Tire Wash	«	TC-3	ESC24			
Entrance / Exit Inspection & Cleaning Facility	«	-	-			
5. General Site Management	Must	select apı	oropriate	BMP f	or each	activity proposed
Materials Management Material Delivery & Storage		WM-1	CA10			
Waste Management Concrete Waste Management		WM-8	CA23			
Solid Waste Management		WM-5	CA20			
Sanitary Waste Management		WM-9	CA24			
Hazardous Waste Management		WM-6	CA21			

Notes:

- 1. When Planting or Hydroseeding are selected for erosion control, the vegetative cover must be planted by August 15th and established by October 1st. If in the opinion of the County Official the vegetative cover is not established by October 1st, additional hydraulic or physical erosion control BMPs will be required.
- 2. These BMPs are temporary measures only when used without planting or hydroseeding. All slopes must have established vegetative cover prior to final grading approval.
- 3. Regional Standard Drawing D-40 Rip Rap Energy Dissipater is also acceptable for velocity reduction.
- 4. Not all grading projects will have every waste identified. The applicant is responsible for identifying wastes that will be on-site and applying the appropriate BMP. For example, if concrete will be used, BMP WM-8 should be selected.

TABLE B: ADDITIONAL CONSTRUCTION BMPs

IADLE D. AD			ONSI	1001	1011	DIVITS
Additional Best		NS cer ks	a Storm- IP k for tion	Will BMP Be Used?		If No, State
Management Practices	(*) If used, these BMPs must be shown on the grading plan.	CALTRANS Stormwater Quality Handbooks	California Storm- water BMP Handbook for Construction	Yes	No	Reason
Erosion Control						
Site Development Considerations		22.4	7001			
Scheduling		SS-1	ESC1			
Preservation of Existing Vegetation	«	SS-2	ESC2			
Other						
(submit description for approval)	«					
Vegetation Stabilization	«	SS-2	_			
Vegetation Buffer Strips	"	33-2	_			
Other	«					
(submit description for approval)						
Physical Stabilization	«	WE-1	ESC21			
Dust Control						
Soil Stabilizers	«	SS-5	-			
Other	«					
(submit description for approval) Diversion of Runoff						
Earthen Dikes	«	SS-9	ESC31			
Ditches and Berms	«	SS-9	_			
Slope Drains	«	SS-11	ESC32			
Temporary Drains & Swales	«	SS-9	ESC31			
Other		55-7	ESCSI			
(submit description for approval)	«					
Velocity Reduction			<u>I</u>	I		
Check Dams	«	SS-4	ESC41			
Slope Terracing	«	-	ESC41			
Other		_	ESC42			
(submit description for approval)	«					
Sediment Control				<u>I</u>		
Brush or Rock Filter		_	ESC53			
Sediment Trap	« «	SC-3	ESC55			
Sediment Trap Sediment Basin	«	SC-2	ESC56			
Other		SC-2	ESCSU			
(submit description for approval)	«					
General Site Management						
Employee & Subcontractor Training		I	C 4 40	l	l	
Materials Management		-	CA40			
Spill Prevention & Control		WM-4	CA12			
Other	1					
(submit description for approval)						
Waste Management						
Contaminated Soil Management		WM-7	CA22			
Other						
(submit description for approval)						
Vehicle and Equipment Management	İ	NG 0	G 1 2 2			
Vehicle & Equipment Cleaning		NS-8	CA30			
Vehicle & Equipment Fueling		NS-9	CA31			
Vehicle & Equipment Maintenance		NS-10	CA32			
Construction Practices		NS-1	_			
Water Conservation		110-1	_			
Structure Construction & Painting	<u> </u>	-	CA3			
Paving Operations	<u> </u>	NS-3	CA2			
Dewatering Operations	ļ	NS-2	CA1			
Other						
(submit description for approval)	<u> </u>					